

# 2020 TIRE SPEC CATALOG

"TIRES DESIGNED FOR CHAMPIONS"

## **NO WARRANTY POLICY**

Hoosier Racing Tire Corp. offers racing tires for sale only upon the conditions and the terms contained in this disclaimer of liability and indemnity. Due to many varied and different conditions which Hoosier Racing Tires and Tubes are exposed and because of the manner in which racing is conducted, Hoosier Racing Tire Corp. makes absolutely **no warranty**, expressed or implied, as to the fitness for a general or particular purpose or of merchantability in connection with any offer of sale of Hoosier Racing Tires and tubes. "HOOSIER RACING TIRES AND TUBES ARE SOLD AS IS." Race tires are not tested or labeled to meet FMVSS 109, 119, 139 or ECE36 Safety Standards. Therefore it is dangerous and illegal to sell race tires for use on public highways. Any person selling Hoosier Racing Tires or Tubes for highway use agrees to indemnity and reimburse Hoosier Racing Tire Corp. for all loss, damage, or liability Hoosier Racing Tire Corp. may suffer because of such sales. Not applicable where prohibited by law. Not following these warnings can cause SERIOUS PERSONAL INJURY OR DEATH. For more information read tire labels, follow manufacturer's warnings as molded in tire sidewalls and visit hoosiertire.com.

# FREEZE WARNING

**Freeze Crack Advisory:** This advisory addresses proper storage and use of Hoosier tires in cold conditions. Hoosier Tires, especially asphalt and hard compound tires, may experience Rubber Cracking if the tires are transported, crushed, flexed or stressed when frozen. The following guidelines are provided to avoid this problem.

- 1. Always store Hoosier Racing Tires indoors at temperatures above 32° F.
- 2. If tires have been subject to 32° F or less, allow them to warm to room temperature (about 70° F) for a minimum of 24 hrs before the tire is mounted, transported or flexed.
- 3. Always use spare tires not intended for future competition to store vehicles for prolonged periods of time or winter transport.
- 4. If below freezing temperatures are expected, please consider shipping tires once more favorable conditions exist.

Do not use tires that have evidence of Freeze Crack Damage.

## **WARNING**

Service Life for Race Tires: Old tires can fail in use, causing loss of vehicle control and personal injury. Environmental conditions like temperature extremes, exposure to sunlight, electric arc, solvents, automotive fluids, and atmospheric pollutants accelerate the aging process. Hoosier Racing Tire strongly recommends that new (sticker) tires should be put in service within 2 years of date of purchase. Used (scuffed) tires have a shorter service life than new (sticker) tires. Poor storage and infrequent use accelerate the aging process.

## **DIRECTION OF ROTATION / MOUNTING INSTRUCTIONS**

## ROTATIONAL GUIDELINES FOR TIRES WITH DIRECTIONAL ARROWS

All Hoosier tires having directional arrows must be mounted so that the tire travels in the direction of the arrow. Hoosier tires having directional arrows will have them on both sidewalls. Directional arrows may not be on a tire that can have both left and/or right side application. All Hoosier tires not having directional arrows should be mounted as detailed below.

## ROTATIONAL GUIDELINES FOR TIRES WITHOUT DIRECTIONAL ARROWS

Every Hoosier race tire has a four character serial code embossed into ONE sidewall of the tire. All Hoosier DOT tires will also have two additional codes as required by the Department of Transportation. (Example: J7AB 4AX8 3710)

## CIRCLE TRACK RACING TIRES:

(Includes both dirt and asphalt tires)

Hoosier tires must be mounted with the serial code located toward the infield.

## **ROAD RACING TIRES:**

(Includes catalog numbers beginning with 43, 44, 45, 46)

In most cases, Hoosier tires used in Road Race applications should be mounted with the serial code toward the center of the vehicle. Once a tire has been run in the proper orientation it is acceptable to remount the tire in the opposite direction to even out the wear.

### DRAG RACING TIRES, INCLUDING DOT DRAG TIRES:

(Includes catalog numbers beginning with 17, 18)

Hoosier drag tires can be mounted to rotate in either direction. Hoosier drag tires can also be flipped or reversed to provide even wear.

## **DIRT BIKE TIRES:**

FRONT TIRES - Mount serial code facing brake caliber.

REAR TIRES - Mount serial code facing sprocket side

## **WARNING - TIRE MOUNTING IS DANGEROUS**

Special Tire Mounting Instructions: Tire mounting should be done ONLY by trained personnel using proper tools and procedures. Failure to follow safe mounting procedures could cause faulty positioning of the tire and cause the assembly to burst with explosive force sufficient to cause SERIOUS PERSONAL INJURY OR DEATH. Always inspect tire for kinked beads or other possible damage that may have occurred in shipping or storage. Clean the rim especially in the bead area before mounting a tire. Lubricate the tire beads as needed with a purpose made tire mounting liquid or paste. Always lock rim on mounting machine or place in safety cage. Use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back.

## **WARNING - VERIFY RIM SIZE**

Verify Correct Wheel and Bead Flange: All tires are designed to be used on wheels that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Some rims are non-standard or damaged and it is necessary to inspect the rim flange to assure proper fit. Consult your specific rim manufacturer to determine if your rim can be used in this application. Never attempt to install and inflate a tire of one bead diameter on a rim or wheel of a different bead diameter. Use of Hoosier Racing Tires on wheels with incorrect bead flanges or wheels that do not meet T&RA standards can cause the assembly to fail and burst with explosive force sufficient to cause SERIOUS PERSONAL INJURY OR DEATH. Use a certified wheel rim disk tape to confirm wheel rim flange size.

## **WARNING - BEAD / RIM SEATING**

When seating beads never exceed maximum bead seating pressure as molded in tire sidewall. Never exceed manufacturer's maximum inflation pressure. Always seat beads with wheel locked to mounting machine or placed in a safety cage. A damaged tire or wheel can fail during bead seating and burst with enough force sufficient to cause **SERIOUS PERSONAL INJURY OR DEATH.** Always use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back. If the beads will not seat at the manufacturers maximum bead seating pressure, STOP, deflate tire, return the tire to the place of purchase.

## **WARNING - NOT FOR HIGHWAY USE**

NOT FOR HIGHWAY USE: All Hoosier Racing Tires including DOT labeled Hoosier Racing Tires are designed for racing purposes only on specified racing surfaces and are not to be operated on public roadways. DOT labeled Hoosier Racing Tires meet Department Of Transportation requirements for marking and performance only and are NOT INTENDED FOR HIGHWAY USE. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and SERIOUS PERSONAL INJURY OR DEATH.

# **WARNING - MISUSE / MISAPPLICATION**

Exception - "PRO STREET" page 20.

Application/Misuse: All Hoosier Racing Tire products are designed for a specific purpose. Consult with Hoosier Racing Tire Corp. for specific fitment and application. Utilizing Hoosier Tires in any form outside of their intended use constitutes MISUSE of the product and can cause SERIOUS PERSON-AL INJURY OR DEATH. Hoosier Racing Tire products are designed and manufactured for racing purposes only, within a closed course designed for organized competition. Not for recreational use. Hoosier Tires should never be used for Off Track Exhibition or for Land Speed Record Vehicles including Jet or Rocket Powered Cars.

# **WARNING - DO NOT ALTER TIRES**

Chemical Treatment of Tires: Hoosier Racing Tires strictly forbids any chemical alteration of the tire carcass and/or tread compound such as tire "soaking" or use of tread "softener." Hoosier Racing Tire strictly forbids the physical defacement (removal, altering or covering), of tire sidewall markings in any manner. Failure to comply with this warning could result in premature or catastrophic tire failure and may result in SERIOUS PERSONAL INJURY OR DEATH.

# **TABLE OF CONTENTS**

| LEAD #   | TIRE   | PAGE #             |
|----------|--|--------------------|
|          | NO WARRANTY POLICY & WARNINGS                        | Inside Front Cover |
|          | Direction of Rotation / Mounting                     |                    |
|          | Instructions   | 3                  |
| 41       | Little Car Asphalt / Mini-Cup                        | 5                  |
| 13       | Midget Asphalt                                       |                    |
| 08/10/37 | Asphalt Short Track                                  |                    |
| 08/09    | Modified / Supers / Sprint Asphalt                   | 7                  |
| 12       | Oval Track D.O.T. Dirt                               |                    |
| 36       | Late Model / E-Mod / Street Stock Dirt               | 8-9                |
| 14       | Eastern Modified / 358 / Sportsman Dirt              |                    |
| 31/38    | Wing Sprint Dirt                                     |                    |
| 31/38    | Non-Wing Sprint Dirt / Silver Crown Short Track Dirt |                    |
| 31       | Silver Crown Dirt / Mile Tracks                      |                    |
| 35       | Midget Dirt / Mini Sprint                            |                    |
| 42       | Modified Midget / Micro Sprint Dirt / Jr. Sprint     |                    |
| 11/15    | Dirt Oval Karting                                    |                    |
| 11       | Treaded Kart   |                    |
| 15       | Asphalt Oval Karting                                 |                    |
| 15       | Asphalt Quarter Midget                               |                    |
| 11       | Dirt Quarter Midget                                  |                    |
| 22       | 5" Sprint / Solo Kart                                |                    |
|          | Super Kart & Enduro                                  |                    |
| 18       | Drag Racing  |                    |
| 18       | Drag Racing - Radial                                 |                    |
| 18       | Drag Bracket Radial                                  |                    |
| 18       | JR Dragster  |                    |
| 17       | D.O.T. Drag - Radials                                |                    |
| 17       | Quick Time Pro D.O.T                                 |                    |
| 17       | Quick Time D.O.T.                                    |                    |
| 28/32    | Racing Tubes & Liner                                 |                    |
| 19       | Pro Street D.O.T. – Radial                           |                    |
| 43       | Circuit Racing Slicks – Bias                         |                    |
| 43       | Circuit Racing Slicks – Radial                       |                    |
| 44       | Circuit Racing Wets – Bias                           |                    |
| 44       | Circuit Racing Wets – Radial                         |                    |
| 44/45/46 | Vintage  |                    |
| 46       | Circuit Racing D.O.T. – Radial                       |                    |
| 46       | Circuit Racing D.O.T. – Radial Wet                   |                    |
| 41/43/44 | Formula Student (FSAE)                               |                    |
| 41/45/44 | Rally  |                    |
| 07       | Dirt Bike  |                    |
| 11/16/42 | ATV / 3 Wheeler                                      |                    |
| 16       | UTV / SxS  |                    |
| 10       | Hoosiar Racing Tira Distributors                     |                    |

# **SEE WARNINGS STARTING ON INSIDE COVER**

Tire rule spec tires may not be listed in this catalog. Please contact local distributor for further information.

REV. 02/20 Second Printing

# **OFF ROAD**

# **DIRT BIKE**

| ITEM<br>Number | TIRE SIZE      | TREAD<br>PATTERN | TREAD<br>WIDTH | APPROX.<br>CIRC. | RECOM.<br>RIM WIDTH | MEASURED<br>RIM WIDTH | SECTION WIDTH | COMPOUND<br>SOFT TO FIRM | APPLICATION     |
|----------------|----------------|------------------|----------------|------------------|---------------------|-----------------------|---------------|--------------------------|-----------------|
| 07000          | 60/100-10      | Motocross Front  | 2.75"          | 48.0"            | 1.5"                | 1.5"                  | 2.75"         | MX30                     | 50cc JR Front   |
| 07005          | 60/100-12      | Motocross Front  | 2.70"          | 53.75"           | 1.5″                | 1.5"                  | 2.70"         | MX30                     | 50cc SR Front   |
| 07010          | 70/100-10      | Motocross Rear   | 3.12"          | 48.75"           | 1.5"                | 1.5"                  | 3.12"         | IMX30                    | 50cc Rear       |
| 07020          | 80/100-12      | Motocross Rear   | 3.70"          | 57.75"           | 1.6"                | 1.6″                  | 3.70"         | MX30                     | 65cc Rear       |
| 07025          | 70/100-17      | Motocross Front  | 3.20"          | 72.75"           | 1.4"                | 1.4"                  | 2.70"         | MX30                     | 85cc Front      |
| 07030          | 90/100-14      | Motocross Rear   | 4.50"          | 68.5"            | 1.6"                | 1.6"                  | 3.65"         | IMX30                    | 85cc Rear       |
| 07100          | 80/100-21      | Motocross Front  | 3.86″          | 88.75"           | 1.6"                | 1.6"                  | 3.86"         | MX25, MX30               | 125, 250, 450cc |
| 07110          | 80/100-21      | Motocross Front  | 3.86"          | 88.75"           | 1.6"                | 1.6"                  | 3.86"         | MX25S, MX30S             | 125, 250, 450cc |
| 07180          | 110/100-18     | Motocross Rear   | 4.70"          | 84.50"           | 1.85-2.15"          | 2.15"                 | 4.70"         | IMX25, IMX30             | 125, 250, 450cc |
| 07192          | 110/90-19 C100 | Motocross Rear   | 4.65"          | 88.75"           | 1.85-2.15"          | 2.15"                 | 4.65"         | IMX25, IMX30             | 125, 250, 450cc |
| 07201          | 120/80-19 C100 | Motocross Rear   | 5.0″           | 85.75"           | 1.85-2.15"          | 2.15"                 | 5.0"          | IMX25, IMX30             | 125, 250, 450cc |
| 07218          | 120/90-18      | Motocross Rear   | 5.10"          | 84.875"          | 2.15"               | 2.15"                 | 5.10"         | IMX25, MX30              | 250, 450cc      |
| 07300          | 110/90-19      | Soft Terrain     | 4.875"         | 86.0"            | 2.15"               | 2.15"                 | 3.875"        | ST1                      | 125, 250, 450cc |



# ATV / 3 WHEELER

| ITEM<br>NUMBER | TIRE SIZE    | TREAD<br>Pattern   | TREAD<br>WIDTH | APPROX.<br>DIA. | APPROX.<br>CIRC. | RECOM.<br>RIM WIDTH | MEASURED<br>RIM WIDTH | SECTION<br>WIDTH | COMPOUND COMPARISON<br>SOFT TO FIRM | APPLICATION     |
|----------------|--------------|--------------------|----------------|-----------------|------------------|---------------------|-----------------------|------------------|-------------------------------------|-----------------|
| 11940          | 12.0x 8.0-6  | Treaded Crossblock | 8.0"           | 12.0"           | 37.5"            | 9-10                | 10"                   | 9.75"            | D10A, D20A, D30A                    | Youth ATV Rear  |
| 11960          | 12.0x 9.0-6  | Treaded Crossblock | 9.0"           | 12.0"           | 38.5"            | 9-10"               | 10"                   | 10.25"           | D10A, D20A, D30A                    | Youth ATV Rear  |
| 16050          | 16.0x 8.5-8  | Small Crossblock   | 8.5"           | 16.0"           | 53.5"            | 8-9"                | 9″                    | 10.5"            | T30                                 | 3 Wheeler       |
| 16105          | 21.0x 6.0-10 | Rib                | 7.0"           | 21.0"           | 66.0"            | 6-8"                | 7                     | 8.25"            | T20                                 | 3 Wheeler Front |
| 16110          | 18.0x11.0-10 | Wide Tri-Trac      | 10.0"          | 18.0"           | 57.0"            | 10"                 | 10"                   | 11.0"            | T10, T20                            | Flat Track & TT |
| 16115          | 18.0x10.0-10 | Trl-Trac           | 9.0"           | 18.0"           | 57.0"            | 9-10"               | 9″                    | 10.5             | RD20, RD30                          | Flat Track & TT |
| 16130          | 18.5x 6.0-10 | Tri-Trac Front     | 6.0"           | 18.5"           | 59.0"            | 5″                  | 5″                    | 7.5"             | T10                                 | Flat Track & TT |
| 16250          | 18.0x 5.5-10 | ATV Front          | 5.5"           | 18.0"           | 57-58"           | 5″                  | 5″                    | 6.6"             | D10, D12,RD20, RD30                 | Flat Track & TT |
| 16275          | 18.5x 8.0-10 | Large Crossblock   | 8.5"           | 18.5"           | 59.0"            | 8"                  | 8″                    | 9.5"             | D12                                 | Flat Track & TT |
| 16300          | 18.0x10.0-10 | Large Crossblock   | 10.0"          | 18.0"           | 58.0"            | 9-10"               | 10"                   | 11.0"            | D12, RD12, RD15, RD20, RD30         | Flat Track & TT |
| 16325          | 18.5x10.0-10 | Large Crossblock   | 10.0"          | 18.5"           | 59.0"            | 10"                 | 10"                   | 10.9"            | D10, RD12, RD15                     | Flat Track & TT |
| 16600          | 20.5x 6.0-10 | MX Front           | 5.0"           | 20.5"           | 63.25"           | 5″                  | 5″                    | 6.5"             | MX 150                              | MX Front        |
| 16700          | 18.0x10.0-8  | MX Rear            | 8.5"           | 18.0"           | 56.5"            | 8"                  | 8″                    | 9.625"           | MX 150, MX200                       | MX Rear         |
| 16800          | 21.0x 7.0-10 | MX Mud Front       | 6.0"           | 21.0"           | 57.5"            | 5″                  | 5″                    | 6.25"            | XC200                               | MX Mud Front    |
| 16900          | 20.0x11.0-9  | MX Mud Rear        | 9.75           | 20.0~           | 62.5             | 8″                  | 8"                    | 10.75            | XC200                               | MX Mud Rear     |
| 42400          | 15.0/ 6.0-8  | ATV Front          | 6.0"           | 15.0"           | 49.0"            | 6"                  | 6″                    | 7.4"             | D12, RD20                           | Flat Track & TT |
| 42450          | 15.0/ 7.0-8  | Small Crossblock   | 7.0"           | 15.0"           | 49.0"            | 6"                  | 6″                    | 7.5"             | RD20                                | Flat Track & TT |
| 42500          | 15.0/ 8.0-8  | Small Crossblock   | 8.0"           | 15.0"           | 49.5"            | 7'                  | 7"                    | 8.5"             | RD20                                | Flat Track & TT |
| 42550          | 16.0/ 8.5-8  | Small Crossblock   | 8.5"           | 16.0"           | 53.5"            | 9"                  | 9"                    | 10.5"            | RD20                                | Flat Track & TT |

# UTV / SxS

| ITEM<br>NUMBER | TIRE SIZE   | TREAD<br>Pattern | TREAD<br>WIDTH | APPROX.<br>DIA. | APPROX.<br>CIRC. | RECOM.<br>RIM WIDTH | MEASURED<br>RIM WIDTH | SECTION WIDTH | COMPOUND COMPARISON<br>SOFT TO FIRM | APPLICATION   |
|----------------|-------------|------------------|----------------|-----------------|------------------|---------------------|-----------------------|---------------|-------------------------------------|---------------|
| 16105          | 21.0x6.0-10 | RIB              | 7.0"           | 21.0"           | 66.0"            | 6-8"                | 7"                    | 8.25"         | H500                                | RZR 170       |
| 16400          | 27.5/8.0-15 | Super Chain Link | 8.0"           | 27.75"          | 87.0"            | 7-8"                | 8″                    | 10.5"         | S500, M500                          | Prod 1000/PS  |
| 16450          | 27.5/8.0-15 | Super Chain Link | 8.75"          | 27.75"          | 87.0"            | 7-9"                | 8″                    | 11.3"         | S500, M500                          | Turbo 1000/PM |
| SOFT           |             |                  |                |                 |                  |                     |                       |               |                                     | FIRM          |

D10 RD12 D12 RD15 RD20 RD30
D10A S500 D20A D30A M500
T10 T20 MX150 MX200 T30

**WARNING:** Not For recreational use. Hoosier ATV Tires are designed and manufactured for racing purpose only. Within a Closed course for organized competitions. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible **SERIOUS PERSONAL INJURY OR DEATH.** 





65465 S.R. 931 + Lakeville, IN 46536 + (574) 784-3152 + Fax: (574) 784-2385

**Hoosier Racing Tire Europe GmbH** Im Zollhafen 18 ◆ Cologne 50678 ◆ Germany ◆ +49 (172) 291-2544 📑 🔯 🛂

## **DISTRIBUTORS**

## **Hoosier Tire Australia**

17 Blind Road, Nelson, N.S.W. 2765 **ℋ** Ph: 02 9679 1990 **ℋ** Fax: 02 9679 1187 ₩ Email:sales@hoosiertire.com.au **H** www.hoosiertire.com.au

## **Max Dumesny Motorsport**

2/35B Lillee Cres, Tullamarine, VIC. 3043 ₩ Ph: 03 9338 7477 ₩ Fax: 03 9338 7476 **ℋ** Email:melb@mdmotorsport.com.au

# "TIRES DESIGNED FOR CHAMPIONS"